

Single Cab Centre Roof Console Install Instructions

NEW MODELS - We're aware that the Sept 2022 onward builds have a camera at the top of the windscreen, the console will clear everything except the camera harness cover. Our own harness covers will cover the factory camera harness and clear the console – if you receive a console without a black cover (see details below on the 2 different models), please contact us and we will send one out.

Please leave the factory cover off when installing the console, so that you can fit our new cover once you receive it. The camera cover can be left in-place with the console fitted.

SEPT 2022 - SEPT 2023 Radar Models = Small harness cover

SEPT 2023 - CURRENT Facelift Models = Large microphone cover

1. REAR LIGHT REMOVAL

To remove the rear light undo the 2 screws and unclip the wiring. Keep one of these screws to use for the earth on the new light.



2. REAR VIEW MIRROR & SLOT

Remove the rear view mirror and place a 40 mm slot in the roof liner between the mirror and the rib.

NOTE. This is for Pre-Radar Models Only

If you have a Facelift Model Single Cab with no UHF please skip Steps 3-7, and proceed from Step 8B



Cruiser Consoles

70 Series Landcruiser Console Specialists

3. GRAB HANDLE REMOVAL & SUN VISORS

Remove grab handles from the left and right front pillars. Also remove the 2 sun visors to make it easier to run the wires under the roof liner.

- TIP: Use a butter knife in the sides of the clips to remove them without damage.



4. ROOF CONSOLE POWER – FIRE WALL

Pictured are the 2 grommets beside the brake booster that can be used to run the power through the fire wall for the UHF power.

There are grommets on the passenger side that can be used for the UHF Antenna.



5. AUXILIARY POWER BOX

This auxiliary power box should be used to power the UHF.

This prevents interference with the Controller Area Network (CAN) bus circuits.



6. PILLAR REMOVAL

When removing the pillar plastic trims, take note of the plastic barb clip at the bottom inside of the trim. If this clip stays in the metal pillar it will need to be removed and put back onto the plastic trim before reinstalling. The wires can then be run up the pillars to the roof console. The most common power and earth is up the driver's side pillar. The UHF Antenna can go up the passenger side pillar from the bulbar.



7. POWER & EARTH SELECTION

Pictured are the fused terminals that provide the easiest power supply for the console. The wires can be brought up through the bottom of the power box and be connected to the (-neg) Earth terminal. You can choose to connect to constant power – 12V battery (BATT) or accessory power – 12V accessory (ACC). i.e. on with the key.



8A. RUNNING WIRES (Pre-Radar Models)

Run the wires from the engine through the pillar, under the roof liner and come out at the slot you previously cut above the rear-view mirror.



8B. RUNNING WIRES (Facelift Models)

Flat Bottom Console

To connect the touch lights to the factory harness, cut the factory plug off and use the wiring and terminals provided (this is a constant power supply).

If you require acc (accessory) power, run the wires up the pillar from the auxiliary box in front of the brake booster (following Steps 4-8B).

UHF Provision Console

Follow Steps 4-8B to run the wiring for the UHF & Lights power supply. The UHF and lights can share the same acc power.



9. MICROPHONE RELOCATION (Facelift Models)

Use a small flat screwdriver to pop the microphone out of its housing. The microphone can then be relocated to inside the cover behind the grille.



Using the double sided tape provided, attach the factory microphone inside the cover behind the grille.



10. UHF INSTALLATION

Remove the brackets from the console and attach them to the UHF (pictured is the GME TX4500 – as this is the most common UHF installed). Use the front set of holes, this helps the brackets clear the console. Tilt the UHF forward before tightening the screws, so that the heads of the screws are at the top of the slot (as pictured).

Slide the UHF in from the top of the console and then attach the brackets to the console.



11. CONNECTING TOUCH LIGHTS TO POWER (All Pre-Facelift Models)

The 2 wires pictured can be connected to the UHF harness (no switch required as the lights are touch lights with sensor in the middle of the light).

For UHF's with a rear microphone outlet, the microphone curly cord can exit the console beside the rear vision mirror (this will help keep the cord out of the drivers' vision and stop it from swinging).



12. REAR LIGHT WIRING

Plug the console harness into the factory harness for the rear lights. Use the saved bolt to screw the earth wire into the old light thread.

Once this has been done the metal tab on the console slides into the rear light hole.

- TIP: Make sure the wires sit above the metal tab, so they do not get crushed.



13. INSTALLING CONSOLE

Facelift Models

The console has been designed to just clear the white plastic tabs protruding from the large hole in the roof liner. If the console just hits on the tabs, then the tab can be filed/ground back slightly to allow the console to clear it.



Pre-Facelift Models

Have an assistant push the console up and back towards the rear of the cab for you to put the rear-view mirror and bolts back into position.



14. INSTALL MICROPHONE COVER (Facelift Models)

Once the console is installed, the microphone cover can be installed using the bolt provided. It picks up a factory thread in the roof frame (please note the bracket must sit above the lip on the review mirror before tightening, otherwise it will foul on the mirror stalk itself and create a gap on the right-hand side).



Cruiser Consoles

70 Series Landcruiser Console Specialists

15. FINAL INSTALL

Turn the ignition on to check that the touch lights turn on and off by touching the centre of the light.

We hope you enjoy your console, and don't forget to check out our other quality products.



CHECKLIST – OFFICE USE ONLY

- ☐ Console Matches Invoice
- ☐ Instructions Match Consoles
- ☐ Touch Light Trims Installed
- ☐ Check UHF Cut-out
- ☐ Harness Cover (Radar Sept 2022-2023 Models)
- ☐ Large Microphone Cover (Facelift Models)
- ☐ Short Touch Light Harness (Facelifts - Flat Bottom Only)

Signed _____